


NO.	PART	MATERIAL
1	BODY	CAST BRONZE ASTM B-62
2	CAP	CAST BRONZE ASTM B-62
3	SCREEN	SEE TABULATION BELOW
4	GASKET	METAL INSERTED GRAPHITE

PRESSURE/TEMPERATURE RATING  
 150 PSI AT 350°F  
 (10 BAR AT 176.6°C)  
 200 PSI AT 150°F  
 (13.7 BAR AT 65.5°C)

SIZE (NOMINAL)	DIMENSIONS				WEIGHT (DRY)		SCREEN			TAG NUMBER(S)	QTY.
	A IN. MM.	B IN. MM.	C IN. MM.	D IN. MM.	LBS.	KGS.	MATERIAL	PERF.	MESH		
1/4" (6mm)	2.75 / 70	2.25 / 57	2.5 / 64	.25 / 6	.75	.34					
3/8" (10mm)	2.75 / 70	2.25 / 57	2.5 / 64	.25 / 6	.75	.34					
1/2" (13mm)	2.75 / 70	2.25 / 57	2.5 / 64	.25 / 6	.75	.34					
3/4" (19mm)	3 / 76	2.56 / 65	2.62 / 67	.37 / 9	1.38	.62					
1" (25mm)	3.75 / 95	2.75 / 70	3.37 / 86	.37 / 9	2.13	.96					
1 1/4" (32mm)	4.43 / 113	3.62 / 92	4.62 / 117	.75 / 19	3.13	1.4					
1 1/2" (38mm)	4.93 / 125	3.87 / 98	5 / 127	.75 / 19	4.5	2					
2" (51mm)	6.12 / 155	5.12 / 130	6.87 / 174	1 / 25	7	3.1					
2 1/2" (64mm)	8.25 / 210	6 / 152	8.75 / 222	1.25 / 32	12.5	5.6					
3" (76mm)	9 / 229	6.75 / 171	9.75 / 248	1.5 / 38	18	8					

CUSTOMER NAME:  
 P.O. NO.

		<b>MUELLER STEAM SPECIALTY</b> A United Dominion Company			
		NAME:	MODEL 351M Y-STRAINER CLASS 125 SCREWED END CONNECTIONS SIZES 1/4" TO 3" CAST BRONZE		
REVISIONS		DRAWN: MM	DATE: 6/18/99	CHECKED: A. D. D.	DATE: 8/23/99
NO.	REV	BY	SIZE <b>A</b>	DWG. NO. <b>AN-351M</b>	REV. <b>0</b>

NOTE: ALL DIMENSIONS ARE SHOWN NOMINAL.  
 UNLESS OTHERWISE SPECIFIED